

AMENDMENTS TO THE CLAIMS:

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Previously Presented) A saw comprising:
 - a housing;
 - a motor supported by the housing and operable to drive a saw blade;
 - a cover selectively connectable to the housing, the cover at least partially covering the saw blade when the cover is connected to the housing; and
 - a quick-locking member connected to one of the housing and the cover and engageable with the other of the housing and the cover to selectively lock the cover to the housing without the use of tools;
 - wherein the quick-locking member is connected to the housing and is engageable with the cover;
 - wherein the quick-locking member has a first position, in which the quick-locking member engages the cover to lock the cover to the housing, and a second position, in which the quick-locking member is disengaged from the cover and the cover is not locked to the housing;
 - wherein the quick-locking member is pivotable between the first position and the second position.

5. (Previously Presented) A saw comprising:
- a housing;
 - a motor supported by the housing and operable to drive a saw blade;
 - a cover selectively connectable to the housing, the cover at least partially covering the saw blade when the cover is connected to the housing;
 - a quick-locking member connected to one of the housing and the cover and engageable with the other of the housing and the cover to selectively lock the cover to the housing without the use of tools;
 - wherein the quick-locking member is connected to the housing and is engageable with the cover;
 - wherein the quick-locking member has a first position, in which the quick-locking member engages the cover to lock the cover to the housing, and a second position, in which the quick-locking member is disengaged from the cover and the cover is not locked to the housing; and
 - a spring engagable with the quick-locking member to releasably retain the quick-locking member in the first position.
6. (Previously Presented) The saw of claim 4, wherein the cover defines a recess, the quick-locking member including a locking portion engageable with the recess to lock the cover to the housing.
7. (Previously Presented) The saw of claim 4, wherein the cover at least partially covers an upper portion of the saw blade.
8. (Previously Presented) The saw of claim 4, wherein the quick-locking member is a latch.

9. (Previously Presented) A saw comprising:
a housing;
a motor supported by the housing and operable to drive a saw blade;
a cover selectively connectable to the housing, the cover at least partially covering the saw blade when the cover is connected to the housing; and
a quick-locking member connected to one of the housing and the cover and engageable with the other of the housing and the cover to selectively lock the cover to the housing without the use of tools;
wherein the quick-locking member includes an over-center biasing latch.
10. (Previously Presented) The saw of claim 4, wherein the housing defines a handle portion gripable by a user, the quick-locking member being connected to the housing near the handle portion.
11. (Previously Presented) The saw of claim 4, further comprising a second locking assembly cooperating with the quick-locking member to selectively lock the cover to the housing.
12. (Previously Presented) A saw comprising:
a housing;
a motor supported by the housing and operable to drive a saw blade;
a cover selectively connectable to the housing, the cover at least partially covering the saw blade when the cover is connected to the housing; and
a quick-locking member connected to one of the housing and the cover and engageable with the other of the housing and the cover to selectively lock the cover to the housing without the use of tools;
wherein the housing includes a hook member, the cover engaging the hook member at a first end of the cover and the quick-locking member engaging the cover at a second end of the cover to connect the cover to the housing.
13. (Previously Presented) The saw of claim 12, wherein the cover includes a ledge engageable with the hook member.

14. (Original) The saw of claim 12, wherein the cover includes a pin engageable with the hook member.

15. (Previously Presented) The saw of claim 4, wherein the quick-locking member includes a first member connected to the housing, a second member connected to the first member and pivotable relative to the first member, and a third member connected to the second member and pivotable relative to the second member, the third member being engageable with the cover to selectively lock the cover to the housing.

16. (Original) The saw of claim 15, wherein the third member is engageable by a user to move the third member into and out of engagement with the cover to lock and unlock, respectively, the cover from the housing.

17. (Previously Presented) The saw of claim 4, wherein the cover is a first cover, wherein the saw further comprises a second cover connected to the housing and disposed between the saw blade and the first cover when the first cover is connected to the housing, the second cover at least partially covering the saw blade when the first cover is both connected to and disconnected from the housing.

18. (Previously Presented) The saw of claim 4, wherein the cover defines a receptacle therein operable to hold fragments of a work piece upon which the saw blade is performing work, fragments being moved into the receptacle by the saw blade as the saw blade rotates during operation.

19. (Previously Presented) The saw of claim 4, wherein the saw is a circular saw.

20. (Previously Presented) The saw of claim 4, further comprising a shoe plate connected to the housing and engageable with a surface of a workpiece to support the saw upon the workpiece, the cover substantially covering the portion of the saw blade above the shoe plate.

21. (Cancelled)

22. (Cancelled)

23. (Currently Amended) The saw of ~~claim 24~~ claim 36, wherein the first cover at least partially covers the saw blade when the second cover is not connected to the housing.

24. (Cancelled)

25. (Currently Amended) The saw of ~~claim 24~~ claim 36, wherein the first cover at least partially covers an upper portion of the saw blade and the second cover completely covers the first cover and at least partially covers the upper portion of the saw blade when the second cover is connected to the housing.

26. (Currently Amended) The saw of ~~claim 24~~ claim 36, wherein the saw blade includes a plurality of teeth, the first cover covering at least some of the plurality of teeth positioned on an upper portion of the saw blade.

27. (Currently Amended) The saw of ~~claim 24~~ claim 36, further comprising a shoe plate connected to the housing and engageable with a surface of a workpiece to support the saw upon the workpiece, and wherein the saw blade includes a plurality of teeth, the first cover substantially covering the teeth on the portion of the saw blade above the shoe plate.

28. (Currently Amended) The saw of ~~claim 24~~ claim 36, wherein the first cover is semicircular in shape.

29. (Cancelled)

30. (Previously Presented) A saw comprising:
a housing;
a motor supported by the housing and operable to drive a saw blade;
a first cover connected to the housing, the first cover at least partially covering the saw blade; and
a second cover selectively connectable to the housing, the second cover at least partially covering the first cover and at least partially covering the saw blade when the second cover is connected to the housing;
wherein the second cover defines a cavity for receiving fragments from a work piece upon which the saw blade operates; and
wherein the housing and the first cover cooperate to define a slot, and wherein the fragments pass through the slot to enter the cavity.

31. (Original) The saw of claim 30, wherein one of the housing and the first cover include a tab operable to deflect the fragments into the cavity.

32. (Original) The saw of claim 31, wherein the tab is disposed at an end of the slot.

33. (Cancelled)

34. (Currently Amended) The saw of ~~claim 24~~ claim 36, wherein the saw is a circular saw.

35. (Currently Amended) The saw of ~~claim 24~~ claim 36, further comprising a shoe plate connected to the housing and engageable with a surface of a workpiece to support the saw upon the workpiece, the second cover completely covering the first cover and substantially covering the portion of the saw blade above the shoe plate.

36. (Currently Amended) A saw comprising:
a housing;
a motor supported by the housing and operable to drive a saw blade;
a first cover connected to the housing, the first cover at least partially covering the
saw blade;
a second cover selectively connectable to the housing, the second cover
completely covering the first cover and at least partially covering the saw blade when the second
cover is connected to the housing;
wherein the first cover is disposed between the saw blade and the second cover
when the second cover is connected to the housing; and
~~The saw of claim 24, further comprising~~ a quick-locking member connected to
one of the housing and the second cover and engageable with the other of the housing and the
second cover to selectively lock the second cover to the housing without the use of tools.

37. (Original) The saw of claim 36, wherein the quick-locking member is a latch.

38. (Original) The saw of claim 36, wherein the quick-locking member includes an
over-center biasing latch.

Claims 39-43 (Cancelled)

44. (Previously Presented) A saw comprising:
a housing;
a motor supported by the housing and operable to drive a saw blade;
a cover selectively connectable to the housing, the cover at least partially covering
the saw blade when the cover is connected to the housing; and
a quick-locking member connected to one of the housing and the cover and
engageable with the other of the housing and the cover to selectively lock the cover to the
housing without the use of tools, the quick-locking member being pivotable between a first
position, in which the cover is locked to the housing, and a second position, in which the cover is
not locked to the housing.

45. (Previously Presented) A saw comprising:
- a housing;
 - a motor supported by the housing and operable to drive a saw blade;
 - a cover selectively connectable to the housing, the cover at least partially covering the saw blade when the cover is connected to the housing;
 - a quick-locking member connected to one of the housing and the cover and engageable with the other of the housing and the cover to selectively lock the cover to the housing without the use of tools, the quick-locking member being movable between a first position, in which the cover is locked to the housing, and a second position, in which the cover is not locked to the housing; and
 - a spring engagable with the quick-locking member to releasably retain the quick-locking member in the first position.